



MOUNTING & ASSEMBLY GUIDE FOR TECHNICALLY BUILT WALL MOUNT FOR LEGO® ICONS TITANIC

TBMNT10294



STEP 1

The wall brackets are designed to be spaced exactly to 16" on center so that you can screw them directly into studs. Use a stud finder to locate your studs and measure 16" apart from the center of the stud. Determine your height where you would like to mount the Titanic and screw in the left or right mount first. Before tightening all the way place a level on top of the mount, ensure its level then tighten it down.

INSTALL BRACKETS 16" ON STUD CENTER



THE TITANIC SHOULD SET WITH THE
SECTIONAL SPLIT LINES ON THE INSIDE OF
THE BRACKETS AS SEEN ABOVE.

STEP 2

After installing the first (left or right) bracket, use a level to align and mark the mounting position for the second bracket. Have someone hold the second bracket in place, ensuring both brackets are level and in line with your stud marks. Mark the holes and install the second bracket.

Before mounting the Titanic, confirm all four screws are fully tightened and the brackets do not move. Perform a final level check on each bracket and across the span of the brackets. If everything is level and secure, mount the Titanic according to the diagram. Using the included LEGO pieces install the Titanic name placard as seen above.

WARNING



WALL ANCHORS ARE INCLUDED WITH THE BRACKETS BUT IS HIGHLY
RECOMMENDED TO INSTALL DIRECTLY INTO STUDS. FAILURE TO PROPERLY
MOUNT WALL ANCHORS OR FOLLOW MOUNTING INSTRUCTIONS COULD RESULT
IN THE SET CRASHING TO THE FLOOR.

